Page 1/9



GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2012

Version number 14

Revision: 08.05.2012

1.1 Product identifier	
Trade name:	004 Osmo Douglas Fir Oil, Natural shade
1.2 Relevant identified uses of	f the substance or mixture and uses advised against
Application of the substance	/ the
preparation	Wood treatment
	Coating compound/ Surface coating/ paint
1.3 Details of the supplier of	the safety data sheet
Manufacturer/Supplier:	Osmo Holz und Color GmbH & Co. KG
	Affhüppen Esch 12
	D-48231 Warendorf
Further information obtainal	ble
from:	Product safety department
	Phone: +49 (0) 251 / 692 - 188
	Fax: +49 (0) 251 / 692 - 462
	e-mail: helmut.starp@osmo.de
1.4 Emergency telephone	
number:	emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in Germa
	and English
TT 1 • 1 ,• 0• ,•	
Hazards identification	

Classification according to	
Directive 67/548/EEC or Directive	e
1999/45/EC	Not applicable.
Information concerning	
particular hazards for human and	d
environment:	The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
Classification system:	The classification is according to the latest editions of the EU-lists and extended by company and literature data.
2.2 Label elements	
Labelling according to EU	
guidelines:	Although this product is not subject to identification regulations, we recommend that
	the safety suggestions are observed.
Safety phrases:	2 Keep out of the reach of children.
	24/25 Avoid contact with skin and eyes.
	26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	46 If swallowed, seek medical advice immediately and show this container or label.
	51 Use only in well-ventilated areas.
	(Contd. on page 2)



(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2012

Version number 14

Revision: 08.05.2012

Trade name: 004 Osmo Douglas Fir Oil, Natural shade

Special labelling of certain	
preparations:	Warning:
	Wash out any used cloth impregnated with this product immediately after use or store
	in an airtight container (danger of self-ignition)
	Contains 2-butanonoxime. May produce an allergic reaction.
	Safety data sheet available for professional user on request.
Additional information:	Observe the general safety regulations when handling chemicals.
	Always wear a dust mask when sanding.
2.3 Other hazards	
Results of PBT and vPvB asse	essment
PBT:	Not applicable.
vPvB:	Not applicable.

3 Composition/information on ingredients

3.2 Chemical characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	25-50%
EC number: 918-481-9	Xn R65	
Index number: 649-327-00-6	R66	
Reg.nr.: 01-2119457273-39	Acute Tox. 3, H331; Asp. Tox. 1, H304	
Additional information:	For the wording of the listed risk phrases refer to section 16.	

4 First aid measures

4.1 Description of first aid measures

General information:	Immediately remove any clothing soiled by the product.
	Take affected persons out into the fresh air.
After inhalation:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
	In case of unconsciousness place patient stably in side position for transportation.
After skin contact:	Immediately wash with water and soap and rinse thoroughly.
	If skin irritation continues, consult a doctor.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:	If swallowed, seek medical advice immediately and show this container or label.
4.2 Most important symptoms an	nd l
effects, both acute and delayed	Headache
	Dizziness
	(Contd. on page 3)

GB -

Page 3/9



(Contd. of page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2012

Revision: 08.05.2012

Version number 14 Trade name: 004 Osmo Douglas Fir Oil, Natural shade 4.3 Indication of any immediate medical attention and special No further relevant information available. treatment needed 5 Firefighting measures 5.1 Extinguishing media Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable Water with full jet extinguishing agents: 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. 5.3 Advice for firefighters **Protective equipment:** Mouth respiratory protective device. Dispose of fire debris and contaminated fire fighting water in accordance with official Additional information regulations. Cool endangered receptacles with water spray. 6 Accidental release measures 6.1 Personal precautions, protective equipment and Wear protective equipment. Keep unprotected persons away. emergency procedures Keep away from ignition sources. Ensure adequate ventilation Inform respective authorities in case of seepage into water course or sewage system. 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. 6.3 Methods and material for containment and cleaning up: Warm water and cleansing agent Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). See Section 13 for disposal information. 6.4 Reference to other sections No dangerous substances are released. 7 Handling and storage 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Keep receptacles tightly sealed. Use only in well ventilated areas.

Prevent formation of aerosols.

GB



(Contd. of page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2012

Version number 14

Revision: 08.05.2012

Trade name: 004 Osmo Douglas Fir Oil, Natural shade

Storage:	
Requirements to be met by	
storerooms and receptacles:	Store in a cool location.
	Store only in the original receptacle.
Information about storage in of	ne
common storage facility:	Do not store together with alkalis (caustic solutions).
	Do not store together with oxidizing and acidic materials.
Further information about	
storage conditions:	Keep container tightly sealed.
	Store in cool, dry conditions in well sealed receptacles.
7.3 Specific end use(s)	No further relevant information available.

8 Exposure controls/personal protection		
Additional information about design of technical facilities:	No further data; see item 7.	
8.1 Control parameters		
Ingredients with limit values that require monitoring at the		
workplace:	The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.	
Additional information:	The lists valid during the making were used as basis.	
8.2 Exposure controls Personal protective equipment: General protective and hygienic		
measures:	Immediately remove all soiled and contaminated clothing	
	Keep away from foodstuffs, beverages and feed.	
	Avoid contact with the eyes and skin.	
	Do not eat, drink, smoke or sniff while working.	
	Do not carry product impregnated cleaning cloths in trouser pockets.	
Respiratory protection:	Use suitable respiratory protective device only when aerosol or mist is formed. Not necessary if room is well-ventilated.	
	Short term filter device:	
	Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 $^{\circ}$ C)).	
Protection of hands:	Protective gloves	
	To avoid skin problems reduce the wearing of gloves to the required minimum.	
	Selection of the glove material on consideration of the penetration times, rates of	
	diffusion and the degradation	
Material of gloves	Nitrile rubber, NBR	
	(Contd. on page 5)	



Printing date 08.05.2012

Version number 14

Revision: 08.05.2012

Trade name: 004 Osmo Douglas Fir Oil, Natural shade

(Contd. of page 4) **Penetration time of glove material** The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

made of the following materials are suitable: Nitrile rubber, NBR As protection from splashes gloves made of the following material language of the splashes
gloves made of the following
materials are suitable: Nitrile rubber, NBR
<i>Eye protection:</i> Goggles recommended during refilling
<i>Body protection:</i> Protective work clothing

9 Physical and chemical properties

9.1 Information on basic physica General Information	u una chemicai properties	
Appearance:		
Form:	Fluid	
Colour:	Light brown	
Odour:	Mild	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	> 180°C	
Flash point:	≥ 63 °C (DIN 53213)	
Ignition temperature:	240°C	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	0.6 Vol %	
Upper:	7.0 Vol %	
Density at 20°C:	0.9 - 0.98 g/cm ³ (DIN 51757)	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Viscosity:		
Kinematic at 20°C:	24 s (ISO 4 mm)	
	> 30 s (ISO 3mm)	
Solvent content:		
VOC (EC)	Not applicable.	



Printing date 08.05.2012

Version number 14

Revision: 08.05.2012

		o Douglas Fir Oil, Natural shade
		(Contd.
9.2 Other information		No further relevant information available.
Stability .	and reacti	ivity
10.1 React	ivity	
	ical stability	
	ecomposition to be avoide	
	oility of haza	
reactions	ning og næsa	Reacts with fabric soaked in the product (e.g. cleaning wool).
	tions to avoi	
	patible mat	
	dous decom	
products:		Formation of toxic gases is possible during heating or in case of fire. Nitrogen oxides (NOx)
		Carbon monoxide and carbon dioxide
Additional	information	n:
		Warning: Wash out any used cloth impregnated with this product immediately after use
		in an airtight container (danger of self-ignition)
Toxicolo	gical infor	rmation
11.1 Inform	nation on to	rmation oxicological effects
11.1 Inforr Acute toxic	nation on to rity:	oxicological effects
11.1 Inforn Acute toxic LD/LC50 v	nation on to rity: values releva	oxicological effects ant for classification:
11.1 Inforr Acute toxic LD/LC50 v 64742-48-5	nation on to city: values releva aliphatic h	oxicological effects ant for classification: hydrocarbons, C10-C13
11.1 Inforr Acute toxic LD/LC50 v 64742-48-9 Oral	nation on to rity: alues releva aliphatic h	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401)
11.1 Inform Acute toxic LD/LC50 v 64742-48-9 Oral Dermal	nation on to sity: palues releva paliphatic h LD50 > LD50 >	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401) > 5000 mg/kg (rat) (OECD Richtlinie 402)
11.1 Inforr Acute toxid LD/LC50 v 64742-48-9 Oral Dermal Inhalative	nation on to sity: Palues releva Paliphatic h LD50 > LD50 > LC50 / 4h >	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401) > 5000 mg/kg (rat) (OECD Richtlinie 402) > 5 mg/l (rat) (OECD Richtlinie 403)
11.1 Inforr Acute toxic LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2-1	nation on to eity: Palues releva D aliphatic h LD50 > LD50 > LC50 / 4h >	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401) > 5000 mg/kg (rat) (OECD Richtlinie 402) > 5 mg/l (rat) (OECD Richtlinie 403) ime
11.1 Inform Acute toxic LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2-1 Oral	nation on to sity: alues releva aliphatic h LD50 > LD50 > LC50 / 4h > butanonoxin LD50 3	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401) > 5000 mg/kg (rat) (OECD Richtlinie 402) > 5 mg/l (rat) (OECD Richtlinie 403) ime 3700 mg/kg (rat)
11.1 Inforn Acute toxid LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2- Oral	nation on to sity: alues releva aliphatic h LD50 > LD50 > LC50 / 4h > butanonoxin LD50 3	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401) > 5000 mg/kg (rat) (OECD Richtlinie 402) > 5 mg/l (rat) (OECD Richtlinie 403) ime
11.1 Inforr Acute toxid LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2-1 Oral Dermal	nation on to sity: alues releva aliphatic h LD50 > LC50 / 4h > butanonoxin LD50 3 LD50 2	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401) > 5000 mg/kg (rat) (OECD Richtlinie 402) > 5 mg/l (rat) (OECD Richtlinie 403) ime 3700 mg/kg (rat)
11.1 Inforr Acute toxid LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2-1 Oral Dermal Inhalative Primary in	nation on to sity: alues releva aliphatic h LD50 > LC50 / 4h > butanonoxin LD50 3 LD50 3 LD50 4 LC50 / 4h >	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401) > 5000 mg/kg (rat) (OECD Richtlinie 402) > 5 mg/l (rat) (OECD Richtlinie 403) ime 3700 mg/kg (rat) 200-2000 mg/kg (rat) >10.5 mg/l (rat) :
11.1 Inforr Acute toxic LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2-1 Oral Dermal Inhalative	nation on to sity: alues releva aliphatic h LD50 > LC50 / 4h > butanonoxin LD50 3 LD50 3 LD50 4 LC50 / 4h >	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401) > 5000 mg/kg (rat) (OECD Richtlinie 402) > 5 mg/l (rat) (OECD Richtlinie 403) ime 3700 mg/kg (rat) 200-2000 mg/kg (rat) >10.5 mg/l (rat) t: At long or repeated contact with skin it may cause dermatitis due to the degrees of the state of
11.1 Inform Acute toxic LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2-1 Oral Dermal Inhalative Primary im on the skim	nation on to sity: values releva aliphatic h LD50 > LD50 > LC50 / 4h > LD50 2 LC50 / 4h > ritant effect: :	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401) > 5000 mg/kg (rat) (OECD Richtlinie 402) > 5 mg/l (rat) (OECD Richtlinie 403) ime 3700 mg/kg (rat) 200-2000 mg/kg (rat) >10.5 mg/l (rat) :: At long or repeated contact with skin it may cause dermatitis due to the deg effect of the solvent.
11.1 Inforr Acute toxid LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2-1 Oral Dermal Inhalative Primary in	nation on to ity: values releva aliphatic h LD50 > LD50 > LC50 / 4h > LD50 2 LC50 / 4h > ritant effect: :	oxicological effects ant for classification: hydrocarbons, C10-C13 > 5000 mg/kg (rat) (OECD Richtlinie 401) > 5000 mg/kg (rat) (OECD Richtlinie 402) > 5 mg/l (rat) (OECD Richtlinie 403) ime 3700 mg/kg (rat) 200-2000 mg/kg (rat) >10.5 mg/l (rat) t: At long or repeated contact with skin it may cause dermatitis due to the degrees of the state of



(Contd. of page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2012

Version number 14

Revision: 08.05.2012

Trade name: 004 Osmo Douglas Fir Oil, Natural shade

Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

12 Ecological information

12.1	Toxi	city	

Aquatic toxicity:			
64742-48-9 aliphatic hydrocarbons, C10-C13			
EC50 / 48h > 1000 mg/l (daphnia) (OECD 202)			
EC50/ 72h > 1000 mg/l (algae)	EC50/ 72h > 1000 mg/l (algae) (OECD 201)		
LC50 / 96h > 1000 mg/l (fish) (LC50 / 96h > 1000 mg/l (fish) (OECD 203)		
96-29-7 2-butanonoxime			
EC50 / 48h 201 mg/l (daphnia)			
IC50 / 72h 11.8 mg/l (algae)			
12.2 Persistence and degradabi	<i>lity</i> No further relevant information available.		
12.3 Bioaccumulative potential	No further relevant information available.		
12.4 Mobility in soil	No further relevant information available.		
Ecotoxical effects:			
Behaviour in sewage processing plants:			
96-29-7 2-butanonoxime			
EC50/ 96h >100 mg/l (fish)			
Additional ecological information:			
General notes:	Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for		
	water		
	Do not allow product to reach ground water, water course or sewage system.		
12.5 Results of PBT and vPvB assessment			
PBT:	Not applicable.		
vPvB:	Not applicable.		
12.6 Other adverse effects	No further relevant information available.		

13 Disposal considerations

13.1 Waste treatment methods	
Recommendation	Must not be disposed together with household garbage. Do not allow product to reach
	sewage system.
	(Contd. on page 8)



Printing date 08.05.2012

Version number 14

Revision: 08.05.2012

		(Contd. of p
European waste catalogue		
08 01 11 waste paint and varnish contain	ing organic solvents or other dangerous substances	
15 01 10 packaging containing residues c	of or contaminated by dangerous substances	
Uncleaned packaging:		
-	osal must be made according to official regulations. ent naphtha	
Transport information		
14.1 UN-Number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Ann	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:	Not dangerous according to the above specifications.	

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:VOC (EC)Not applicable.15.2 Chemical safety assessment:A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

⁻ GB



Printing date 08.05.2012

Version number 14

Revision: 08.05.2012

Trade name: 004 Osmo Douglas Fir Oil, Natural shade

	(Contd. of page
Relevant phrases	H304 May be fatal if swallowed and enters airways.
	H331 Toxic if inhaled.
	R65 Harmful: may cause lung damage if swallowed.
	R66 Repeated exposure may cause skin dryness or cracking.
Department issuing MSDS:	product safety department
Contact:	Hr. Dr. Starp
* Data compared to the previous	
version altered.	